

Get the Royal Edge Advantage with RPI



Royal Edge Termination Bar

ROYAL EDGE PRODUCTS

DESCRIPTION

RPI Termination Bar is a high strength, aluminum bar with installation holes every 6 inches on center. Termination Bar is used when terminating Royal Edge EPDM, Re-Flex EPDM, and Re-Flex TPO to walls, fascia, and other details which require a mechanical termination of the membrane. Use approved fasteners that are appropriate for specific substrates.



THE RPI ROYAL EDGE ADVANTAGE

- Lightweight, high strength Aluminum.
- Easy to install 10ft. bars.

APPLICATION INSTRUCTIONS

Use Water Cut-Off and Lap Caulk where required, (see installation specification manual). To minimize bowing, RPI Termination Bar should be secured starting at one end of the bar, installing to the other end; or beginning in the middle and installing towards both ends. Do not overlap the bar. Leave a minimum 1/8 inch space between bars for expansion. Use only approved fasteners that are appropriate for specific substrates.

PACKAGING

50 - 10 ft. pieces per cardboard tube

STORAGE

Store in dry area, protected from weather.

PRECAUTIONARY DATA

Do not overlap Batten Bar. Check for sharp edges or burs on bar before installation. Termination Bar should be stored in original cardboard shipping containers.

Typical Properties and Characteristics

Material	Aluminum
Corrosion Resistance Length	Meets FM 4470 Criteria
Width	1.0 inch
Thickness	.0448" - .0510"
Holes	6 inches O.C.

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.